

imagePROGRAF iPF770 MFP L36e

ACCELERATE PRODUCTIVITY WITH THIS CONVENIENT LARGE FORMAT MULTIFUNCTION PRINTER.

Introducing the iPF770 MFP L36e – an affordable, intuitive, network-compatible large format printer, compact and lightweight enough to integrate into small office environments with ease.



KEY FEATURES:

- Simplified PC-less scan-to-copy operation drives efficiency
- Flexible workflow options – scan to USB, network, or cloud
- Easy operation via touch screen control panel
- Slender 24-inch footprint requires minimal office space
- Affordable operation thanks to 5-colour dye-and-pigment ink system
- Productivity-boosting scan speeds of up to 3 inches per second
- Crisp 600-dpi optical resolution
- Support for a variety of file formats, including TIFF, PDF and JPEG

PRODUCT RANGE



Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF iPF770 MFP L36e

SCANNER

| | |
|---|---|
| Scan Technology | SingleSensor with multiple LED illumination |
| Optical Resolution | 600dpi |
| Scan speed | COPY 300/300dpi Draft = 1inch/sec colour, 3inch/sec mono 300/600dpi Standard = 1inch/sec colour, 3inch/sec mono 600/600dpi Best = 0.5inch/sec colour, 1.5inch/sec mono |
| Scan Modes | SCAN 200dpi Draft = 1inch/sec colour, 3inch/sec mono 300dpi Standard = 0.5inch/sec colour, 1.5inch/sec mono 600dpi Best = 0.33inch/sec colour, 1inch/sec mono Scan to USB - RGB/Greyscale/BW, TIFF Scan to PC - RGB/Greyscale/BW, Tiff, Jpeg, PDF, TiffG4 Copy - RGB/Greyscale/BW Copy & Archive - RGB/Greyscale/BW, Tiff, Jpeg, PDF, TiffG4 |
| Max scan width | 36" / 914.4mm |
| Max document width | 38" / 965.2mm |
| Max scan length | 109" / 2768mm |
| Max & Min Document thickness | Min = 0.07mm Max = 0.5mm |
| Scan accuracy | Accuracy 0.2% +/-1 pixel |
| Weight of scanner | 6.56kg (14.5lbs) without Doc return guide |
| Dimensions width | 1238mm |
| Dimensions height | 131mm |
| Dimensions depth | Without Doc Return Guide - Paper tray folded: 146mm Without Doc Return Guide - Paper Tray flat: 193mm With Doc Return Guide - Paper tray folded: 206mm With Doc Return Guide - Paper Tray flat: 253mm |
| Power Supply | External PSU: Input: 100 - 240V, 50-60Hz Output: 3.42A at 19V |
| Max Power consumption | Standby (sleep): 0.6W Idle: 11.7W Scanning: 17.5W |
| Scan to USB | USB2, 128GB FAT32 |
| Scan to Network - Scan App Le | Sets scan directory and file type. OS compatibility : Windows7,8,10(32/64bit) |
| Control Panel UI | 3" touch screen display |
| Languages for Scan App Le | English/French/German/Italian/Spanish/Russian/Portuguese/Czech/Polish |
| Environment | Temp: 10-35C Humidity: 10-90% |
| Acoustic noise | 50.6dB gray scan |
| Environment Certificates | Energy Star Europe : CE mark, Russia : EAC, Other countries : CB Certification |
| What's in the Box? | <ul style="list-style-type: none">• Le scanner• Printer mounting brackets, fixings & 3mm tool• 2 feet for desktop use• 2 paper edge guides & paper refeed preventers• 1 Document return guide• Calibration target• CD for Scan App Le software CD for Scan App Le software (includes PDF documentation: Le Scanner User Manual and Icon Guide per language and Quick Start Guide)• User Manual and Icon Guide per language and Quick Start Guide)• Le Scanner Quick Start Guide.• Ethernet cable (2 meter)• Power Supply• Regional - Mains power cord(s) (2 meter) |

Notes & recommendations

| | |
|---------------|---|
| Note 1 | Maximum number of supported iPF printers = 15 Maximum number of PCs running Scan App Le = 15 |
|---------------|---|

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and R: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

PRINTER

| | |
|--------------------------------------|--|
| Printer Type | 5 Colour - 36"/914.4 mm |
| Print Technology | Canon BubbleJet on Demand 6 colours integrated type (6 chips per print head x 1 print head) |
| Number of Nozzles | Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each colour |
| Print Resolution | 2400 dpi x 1200 dpi |
| Nozzle Pitch | 1200 dpi x 2 includes Non-firing nozzle detection and compensation system |
| Guaranteed Minimum Line Width | 0.02 mm |
| Line Accuracy | ±0.1 % or less |
| Ink Droplet Size | 4 Picoliter per colour |
| Ink Capacity | Bundled Starter Ink: C, M, Y, Bk, MBK 90ml Sales Ink: C, M, Y, Bk, MBK 130ml |
| Ink Type | Dye/Pigment Reactive Ink: Cyan, Magenta, Yellow, Black Pigmen ink: 2 x Matte Black |
| Printer OS Compatibility | Windows 32 bit - XP, Vista, 7, 8, 8.1 & 10 Server 2003 / 2003R2, Server 2008 Windows 64 bit - Vista, 7, 8, 8.1 & 10 Server 2003 / 2003R2, Server 2008 / 2008R2, Server 2012 / 2012R2 Mac: OSX - 10.6.8 - 10.10.x |
| Printer Languages | GARO (Graphic Arts language with Raster Operations), HP-GL/2, HP RTL |
| Standard Interfaces | USB 2.0 High-Speed IEEE 802.3 10base-T IEEE 802.3u 100base-TX / Auto-Negotiation IEEE 802.3ab 1000base-T / Auto-Negotiation IEEE 802.3x Full Duplex IEEE 802.3az EEE |
| Standard Memory | 256MB |
| Media Width | Roll paper: 10" / 254 mm - 36" / 914.4 mm Cut sheet: 8" / 203.2 mm - 36" / 914.4 mm |
| Media Thickness | Roll Unit: 0.07 mm - 0.8 mm Top Loading Manual Feed: 0.07 mm - 0.8 mm |
| Maximum Printable Length | Roll: 18m (varies according to the OS and application) Cut Sheet: 1.6m |



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2017