

Océ VarioStream 7110

Océ VarioStream 7170

Flexible entry into continuous feed production

Designed for low-to-mid volume printing, the Océ VarioStream 7100 series is a compact, black-and-white, continuous feed simplex printer family with impressive media versatility and a speed of up to 172 ppm.

**MEDIA VERSATILITY AND
APPLICATION FLEXIBILITY**

**AUTOMATIC PAPER LOADING
AND RESOLUTION DETECTION**

**PROOFING / BACKUP DEVICE FOR
HIGH VOLUME CONTINUOUS FEED
B/W PRINTERS**

LARGE TOUCH SCREEN INTERFACE

**INTEGRATES WITH INDUSTRY
STANDARD WORKFLOWS**



Entry into continuous feed printing

Designed for low-to-mid volume printing, the Océ VarioStream 7100 series is a compact, black-and-white, continuous feed, simplex production printing family with a print speed of up to 172 ppm.

Diverse media

The Océ VarioStream 7100 series is based on non-contact flash fusing technology which operates at a very low temperature compared to normal heat and pressure fusing. The flash fusing technology and its straight paper path enables you to print on the widest variety of media types available in continuous feed printing. For example, labels, plastic cards, carbonless paper, pre-printed forms with cards, and coated paper can all be loaded - ideal for specialist providers looking to add real diversity to their production workflow.

Easy operation

The large touch screen operation panel makes operation effortless, minimising job set-up times and boosting overall productivity. And with an automatic paper loading system which makes changing media quick and simple too, the Océ VarioStream 7100 series is perfect for both short-run and quick-change print jobs. The printer's automatic resolution detection system enables you to instantly combine text at 240 dpi, logos at 300 dpi and illustrations at 600 dpi, without carrying out manual adjustments or conversions beforehand.

Seamless workflow integration

Powered by the Océ SRA® controller which supports the latest advancements in AFP/IPDS (IS/3), the Océ VarioStream 7100 can be integrated into the colour workflow of all the newest Océ full-colour capable print engines. With the support of native PCL6, and PDF via the incorporated Adobe PDF Print Engine 2.6 and the Océ PRISMA® software suite, the Océ VarioStream 7100 integrates seamlessly into any industry-standard workflows.

Canon

Technical Specifications:
Océ VarioStream 7100 series

Océ VarioStream 7110

Océ VarioStream 7170

TECHNOLOGY

Print Technology	LED technology, dry toner
Fusing Technology	Flash fusing
Functionality	Simplex
Operating	Océ look & feel user interface
Paper transport	Pin feed
Paper input	Stack, jumbo stack, unwinder
Paper output	Integrated stacker, rewinder or any kind of post processing with Type1 Interface
Print resolution	600×600 dpi
Print speed A4 pages per minute	Océ VarioStream 7110: 108 pages per minute Océ VarioStream 7170: 172 pages per minute
Duty cycle million A4 per month	Océ VarioStream 7110: 0.8 - 3 million pages per month Océ VarioStream 7170: 1 - 5 million pages per month

PAPER

Print width	Max. 17" (max. 432 mm)
Page length	7"-20" (178 mm - 508 mm)
Paper width	7"-18" (178 mm - 457 mm)
Form length	Internal stacker: 7"-14" (178 mm - 356 mm), Optional: external stacker 7"-20" (178 mm - 508 mm)
Paper weight	64-209 gr/m ² (64-120 gr/m ² with internal stacker*)
Substrates	Preprinted, laser and recycled paper, foils, labels, thin plastic cards**

POWER REQUIREMENTS

PRINTING UNIT

Connection (EU)	Océ VarioStream 7110: 230 V ±10%, 47-62 Hz, single phase Océ VarioStream 7170: 400 V ±10%, 47-62 Hz, three phase
Consumption printing (EU)	Océ VarioStream 7110: 4.55 kVA Océ VarioStream 7170: 6.37 kVA
Consumption idle (EU)	0.3 kVA

ENVIRONMENTAL

Temperature	Rated range 15-25 °C, limited range 10-30 °C
Humidity	Rated range 35-70%, limited range 30-80% r.h.
Elevation	Sea level to 2100 m
Operating noise	Maximum 65 dB (idle 51 dB)

WORKFLOW

Controller	SRA Controller
Printer data format	AFP/IPDS (IS/3), PCL 6
Print manager (optional)	Océ PRISMAproduction* / Océ PRISMA*spool
Connectivity	Gigabit Ethernet (copper)

OPTIONS

Post Processing Interface (Type 1)	Available
Adobe PDF Print Engine 2.6	Available
Operator attention light	Available

PHYSICAL DATA

Dimensions (L × W × H)	1,725 mm × 1,090 mm × 1,460 mm
Weight (EU):	Océ VarioStream 7110: 470 kg Océ VarioStream 7170: 570 kg

Footnotes

- * Paper with higher weight could be used after positive test
** Substrates have to fulfill the print media specification