

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 02.04.2012

Version number 45

Revision: 02.04.2012

### 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** MULTIFOAM STRONG
- **Article number:** 140.1126.0
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation** Cleaning agent/ Cleaner
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
MOTIP DUPLI B.V.  
Wolfraamweg 2  
NL- 8471 XC Wolvega  
The Netherlands  
Tel: +31 (0)561 694400  
Fax: +31 (0)561 694411  
e-mail info@nl.motipdupli.com
- **Further information obtainable from:** QHSE Department
- **Emergency telephone number:** Tel: +31 (0)561 694400 (08.00 / 17.00)

### 2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



F+; Extremely flammable

R12: Extremely flammable.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **Label elements**

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

- **Code letter and hazard designation of product:**

F+ Extremely flammable

- **Risk phrases:**

12 Extremely flammable.

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.04.2012

Version number 45

Revision: 02.04.2012

**Trade name: MULTIFOAM STRONG**

(Contd. of page 1)

**· Safety phrases:**

- 2 Keep out of the reach of children.  
 16 Keep away from sources of ignition - No smoking.  
 23 Do not breathe aerosol.  
 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
 46 If swallowed, seek medical advice immediately and show this container or label.  
 51 Use only in well-ventilated areas.

**· Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

**· Classification in accordance with Directive 75/324/EEC: Extremely flammable****· Other hazards****· Results of PBT and vPvB assessment**

· **PBT:** Not applicable.



















· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

**· Chemical characterization: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

**· Dangerous components:**

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| CAS: 67-63-0<br>EINECS: 200-661-7  | propan-2-ol<br> Xi R36<br> F R11<br>R67<br>-----<br> Flam. Liq. 2, H225<br> Eye Irrit. 2, H319; STOT SE 3, H336 | 10-12.5% |
| CAS: 74-98-6<br>EINECS: 200-827-9  | propane<br> F+ R12<br>-----<br> Flam. Gas 1, H220<br> Press. Gas, H280                                                                                                                             | 2.5-5%   |
| CAS: 106-97-8<br>EINECS: 203-448-7 | butane<br> F+ R12<br>-----<br> Flam. Gas 1, H220<br> Press. Gas, H280                                                                                                                              | 2.5-5%   |
|                                    | isobutaan (bevattend < 0,1 % butadien (203-450-8))<br> F+ R12<br>-----<br> Flam. Gas 1, H220<br> Press. Gas, H280                                                                                  | 2.5-5%   |
| CAS: 107-98-2<br>EINECS: 203-539-1 | 1-methoxy-2-propanol<br>R10-67<br>-----<br> Flam. Liq. 3, H226                                                                                                                                                                                                                                                                                                           | 1-2.5%   |
|                                    | ammonia 25%<br> C R34<br> N R50<br>-----<br> Skin Corr. 1B, H314<br> Aquatic Acute 1, H400                      | 0.1-1%   |

**· Regulation (EC) No 648/2004 on detergents / Labelling for contents**

aliphatic hydrocarbons

5 - 15%

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.04.2012

Version number 45

Revision: 02.04.2012

Trade name: **MULTIFOAM STRONG**

(Contd. of page 2)

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

#### 4 First aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.04.2012

Version number 45

Revision: 02.04.2012

Trade name: **MULTIFOAM STRONG**

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

## \* 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

### · **Ingredients with limit values that require monitoring at the workplace:**

#### 67-63-0 propan-2-ol

|        |                                                                                                        |
|--------|--------------------------------------------------------------------------------------------------------|
| WEL () | Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm<br>Long-term value: 999 mg/m <sup>3</sup> , 400 ppm |
|--------|--------------------------------------------------------------------------------------------------------|

#### 106-97-8 butane

|        |                                                                                                                                                       |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| WEL () | Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm<br>Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm<br>Carc (if more than 0.1% of buta-1.3-diene) |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------|

#### 107-98-2 1-methoxy-2-propanol

|        |                                                                                                             |
|--------|-------------------------------------------------------------------------------------------------------------|
| WEL () | Short-term value: 560 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 375 mg/m <sup>3</sup> , 100 ppm<br>Sk |
|--------|-------------------------------------------------------------------------------------------------------------|

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:** Not required.
- **Protection of hands:** Not required.
- **Material of gloves** Not required.
- **Penetration time of glove material** Not required.
- **Eye protection:** Not required.

## \* 9 Physical and chemical properties

### · **Information on basic physical and chemical properties**

#### · **General Information**

##### · **Appearance:**

|                  |                                    |
|------------------|------------------------------------|
| Form:            | Aerosol                            |
| Colour:          | According to product specification |
| Odour:           | Characteristic                     |
| Odour threshold: | Not determined.                    |

|           |                 |
|-----------|-----------------|
| pH-value: | Not determined. |
|-----------|-----------------|

##### · **Change in condition**

|                              |                             |
|------------------------------|-----------------------------|
| Melting point/Melting range: | Undetermined.               |
| Boiling point/Boiling range: | Not applicable, as aerosol. |

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.04.2012

Version number 45

Revision: 02.04.2012

Trade name: **MULTIFOAM STRONG**

(Contd. of page 4)

|                                                     |                                                                                                 |
|-----------------------------------------------------|-------------------------------------------------------------------------------------------------|
| · <b>Flash point:</b>                               | < 0°C (< 32 °F)<br>Not applicable, as aerosol.                                                  |
| · <b>Flammability (solid, gaseous):</b>             | Not applicable.                                                                                 |
| · <b>Ignition temperature:</b>                      | 425°C (797 °F)                                                                                  |
| · <b>Decomposition temperature:</b>                 | Not determined.                                                                                 |
| · <b>Self-igniting:</b>                             | Product is not selfigniting.                                                                    |
| · <b>Danger of explosion:</b>                       | Product is not explosive. However, formation of explosive air/<br>vapour mixtures are possible. |
| · <b>Explosion limits:</b>                          |                                                                                                 |
| Lower:                                              | 2.0 Vol %                                                                                       |
| Upper:                                              | 12.0 Vol %                                                                                      |
| · <b>Vapour pressure at 20°C (68 °F):</b>           | 3500 hPa (2625 mm Hg)                                                                           |
| · <b>Density at 20°C (68 °F):</b>                   | 0.918 g/cm <sup>3</sup> (7.661 lbs/gal)                                                         |
| · <b>Relative density</b>                           | Not determined.                                                                                 |
| · <b>Vapour density</b>                             | Not determined.                                                                                 |
| · <b>Evaporation rate</b>                           | Not applicable.                                                                                 |
| · <b>Solubility in / Miscibility with water:</b>    | Not miscible or difficult to mix.                                                               |
| · <b>Segregation coefficient (n-octanol/water):</b> | Not determined.                                                                                 |
| · <b>Viscosity:</b>                                 |                                                                                                 |
| Dynamic:                                            | Not determined.                                                                                 |
| Kinematic:                                          | Not determined.                                                                                 |
| · <b>Solvent content:</b>                           |                                                                                                 |
| Organic solvents:                                   | 21.6 %                                                                                          |
| Water:                                              | 78.0 %                                                                                          |
| · <b>Solids content:</b>                            | 0.4 %                                                                                           |
| · <b>Other information</b>                          | No further relevant information available.                                                      |

## 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

### · LD/LC50 values relevant for classification:

#### 67-63-0 propan-2-ol

|        |            |                            |
|--------|------------|----------------------------|
| Oral   | LD50       | 5045 mg/kg (rat)           |
| Dermal | LD50       | 12800 mg/kg (rabbit)       |
|        | LC50 / 4 h | 30 mg/m <sup>3</sup> (rat) |

(Contd. on page 6)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.04.2012

Version number 45

Revision: 02.04.2012

**Trade name: MULTIFOAM STRONG**

(Contd. of page 5)

**106-97-8 butane**

|            |                             |
|------------|-----------------------------|
| LC50 / 4 h | 658 mg/m <sup>3</sup> (rat) |
|------------|-----------------------------|

**107-98-2 1-methoxy-2-propanol**

|        |             |                                           |
|--------|-------------|-------------------------------------------|
| Oral   | LD50        | 5660 mg/kg (rat)                          |
| Dermal | LD50        | 13000 mg/kg (rabbit)                      |
|        | LC50 / 4 h  | 55 mg/m <sup>3</sup> (rat)                |
|        | LC50 / 96 h | 4600-10000 mg/l ( <i>Leuciscus idus</i> ) |

**ammonia 25%**

|      |            |                             |
|------|------------|-----------------------------|
| Oral | LD50       | 350 mg/kg (rat)             |
|      | LC50 / 4 h | 5.1 mg/m <sup>3</sup> (rat) |

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

**12 Ecological information**· **Toxicity**· **Aquatic toxicity:****67-63-0 propan-2-ol**

|                       |                                     |
|-----------------------|-------------------------------------|
| EC50 / 48 h           | 13299 mg/l ( <i>daphnia magna</i> ) |
| LC50 / 96 h (dynamic) | 4200 mg/l (fish)                    |

**107-98-2 1-methoxy-2-propanol**

|             |                                           |
|-------------|-------------------------------------------|
| EC50        | >1000 mg/l ( <i>actief slib</i> )         |
| EC50 / 48 h | 23300 mg/l ( <i>daphnia magna</i> )       |
| LC50 / 96 h | 20800 mg/l ( <i>Pimephales promelas</i> ) |

**ammonia 25%**

|      |                                    |
|------|------------------------------------|
| LC50 | 25.4 mg/l ( <i>daphnia magna</i> ) |
|------|------------------------------------|

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

|           |          |
|-----------|----------|
| 20 01 13* | solvents |
|-----------|----------|

(Contd. on page 7)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.04.2012

Version number 45

Revision: 02.04.2012


Trade name: **MULTIFOAM STRONG**

(Contd. of page 6)


|           |                                                                                                                           |
|-----------|---------------------------------------------------------------------------------------------------------------------------|
| 15 01 04  | metallic packaging                                                                                                        |
| 15 01 11* | metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers |

- **Uncleaned packaging:**
- **Recommendation:** Non contaminated packagings may be recycled.

### 14 Transport information

- **UN-Number**
- **ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **Transport hazard class(es)**
- **ADR**
- 
- **Class** 2 5F Gases.
- **Label** 2.1

---

- **IMDG, IATA**
- 
- **Class** 2.1
- **Label** 2.1
- **Packing group**
- **ADR, IMDG, IATA** Void
- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Warning: Gases.
- **Danger code (Kemler):** -
- **EMS Number:** F-D,S-U
- **Segregation groups** Alkalis
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:**

---

- **ADR**
- **Limited quantities (LQ)** 1L
- **Transport category** 2
- **Tunnel restriction code** D
- **UN "Model Regulation":** UN1950, AEROSOLS, 2.1

GB

(Contd. on page 8)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.04.2012

Version number 45

Revision: 02.04.2012

Trade name: **MULTIFOAM STRONG**

(Contd. of page 7)

**15 Regulatory information**

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Relevant phrases**

H220 Extremely flammable gas.  
 H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H280 Contains gas under pressure; may explode if heated.  
 H314 Causes severe skin burns and eye damage.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H400 Very toxic to aquatic life.

R10 Flammable.  
 R11 Highly flammable.  
 R12 Extremely flammable.  
 R34 Causes burns.  
 R36 Irritating to eyes.  
 R50 Very toxic to aquatic organisms.  
 R67 Vapours may cause drowsiness and dizziness.

- **Department issuing MSDS:** QHSE Department

- **Contact:**

Mrs. D. Kleistra  
 Mrs. A. van der Veen

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 ICAO: International Civil Aviation Organization  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent

- **\* Data compared to the previous version altered.**

GB